






RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS





MODEL CODE:

DCB0-00110- A A PB BK S Q 4



- (1):Series type:DIP DC POWER JACK.
- (2):Series No.
- (3):Schematic option: A , B
- (4):Center pin diameter:  
A=φ0.65
- (5):Material of housing:  
PB=PBT (Standard)
- (6):Housing color:  
BK=Black
- (7):Terminal plating  
S=Silver(Ag)
- (8):Special option:  
0=No special opion
- (9):Packing mode:  
4=Bag packing

SPECIFICATION

- 1.Rating : DC 12V 2A;
- 2.Contact resistance: ≤30mΩ;  
After test:≤50mΩ
- 3.Insulation resistance: ≥100MΩ (500VDC);  
After test:≥50MΩ
- 4.Withstand voltage: 500VAC ;
- 5.Insertion and extraction force: 3N-30N;
- 6.life test: 5,000 cycles;
- 7.Operation temperature range:-20°C~70°C;
- 8.Preservative temperature range:-40°C~85°C;



RECOMMENDED P.C.B. LAYOUT  
UNSPECIFIED TOLERANCE:±0.05  
(BOTTOM VIEW)



○: ITEM NO. □: TERMINAL NO.

NO.	PARTS	MATERIAL	Q'TY	FINISHING	TOLERANCE	ANGLES	UNITS	东莞市铀高电子制品有限公司				
④	Shunt terminal ③	Brass t=0.3	1	Silver Plating	±0.3	±2'	mm	TITLE: DIP DC POWER JACK PART NO.: DCB0-00110 DR: Ricky 2019/03/07 DWG NO.: AB0-00110 CHKD: Ricky 2019/03/07 APPD:				
③	Tip spring ②	Beryllium bronze t=0.25	1	Silver Plating			MAT'L					SEE NOTE
②	Center pin ①	Bronze	1	Silver Plating			FINISH					SEE NOTE
①	Housing	PBT	1	Black			Q'TY					SEE NOTE
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.				SCALE	SHEET	REV.	CUSTOMER DRAWING
									1:1	1/1	A	