







RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

MODEL CODE





DIMENSIONS



P.C.B LAYOUT
BOTTOM VIEW

CIRCUIT DIAGRAM


GEI Type



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.3A 50V DC
CIRCUIT	4P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	SHORTING
TRAVEL	2mm
OPERATING FORCE	300±100gf
OPERATING LIFE(cycles)	10,000



8					WITHIN 1.5mm: ±0.1mm	UNITS	mm	东莞市铀高电子制品有限公司						
7					OVER 1.5mm: ±0.2mm	MAT'L								
6	SPRING PLATE	SUS	1	NATURAL		SEE NOTE		TITLE:	SLIDE SWITCH / HORIZONTAL			PART NO.:	SK-42D01	
5	CONTACT CLIP	PBS STRIP	4	Ag PLATED				DR:	Ricky 2016/07/19			DWG NO.:	ADL-42D01	
4	TERMINAL	BRASS STRIP	12	Ag PLATED				CHKD:	Ricky 2016/07/19			SCALE	3:1	
3	BASE	PHENOLIC RESIN	1	NATURAL				APPD:			SHEET	1/1	REV.	A
2	FRAME	STEEL STRIP	1	Ni PLATED							CUSTOMER	DRAWING		
1	KNOB	POM	1	BLACK										
NO.	PARTS	MATERIAL	Q'TY	FINISHING										

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.