






RoHS
Compliant
2002/95/EC


REV.	ECN.	NO.	APPD.

DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



CIRCUIT DIAGRAM



PRODUCT IMAGE



MODEL CODE

YT-1109V -

H	
-	3.0
A	6.2
B	4.0

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.25 ± 0.1mm	
Operating Force	160±30gf	250±50gf
Operating Life(cycles)	100,000	



.X ±0.3 X. ±2'

UNITS mm


MAT'L

SEE NOTE

FINISH

SEE NOTE

Q'TY



东莞市铀高电子制品有限公司

TITLE:
TACT SWITCH

PART NO.:
YT-1109V

DR: Ricky 2014/03/28

DWG NO.:
ASI-1109V

CHKD: Ricky 2014/03/28

APPD:

SCALE	SHEET	REV.	CUSTOMER
1:1	1/1	A	DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.