









RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.

### DIMENSIONS



### Structure chart



### 1.Functional spec

1.1 Rated Voltage	DC30V
1.2 Rated Current	50mA
1.3 Contact Resistance	≤100mΩ(Initial value)
1.4 Operating Force	50~100gf
1.5 Bounce Time	
1.6 Free Position	7.45±0.2mm
1.7 Operating Position	7.0±0.2mm
1.8 Position Travel	
1.9 Return Force	

### 2.Reliable Rating

2.1 Mechanical Life	100,000 CYCLES
2.2 Electrical Life	100,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC250V
2.4 Withstand Voltage	AC600V 1 minute
2.5 Soldering Technic	Hand Soldering
2.6 Operating Temper	-20°C ~ +70°C
2.7 Ambient Humidity Used	<85%RH

### Material list

NO.	PARTS	MATERIAL	Q'TY	FINISHING
8				
7	Thimble	PBT	1	
6	Spring	SWP	1	
5	Spring Plate	SUS301	1	
4	Terminal	C2680	2	
3	Base	PBT	1	
2	Case	PBT	1	
1	Button	PBT	1	

Tolerance:±0.2  
UNITS mm  
MAT'L  
SEE NOTE  
FINISH  
SEE NOTE  
Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

**东莞市铀高电子制品有限公司**

TITLE: TACT SWITCH      PART NO.: YT-00TL

DR: Ricky 2017/7/20      DWG NO.: ATD-0TL-60G

CHKD: Ricky 2017/7/20

APPD:

SCALE	SHEET	REV.	CUSTOMER
1:1	1/1	A	DRAWING