









RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



Structure chart



1.Functional spec

1.1 Rated Voltage	DC30V
1.2 Rated Current	50mA
1.3 Contact Resistance	≤100mΩ(Initial value)
1.4 Operating Force	60~110gf
1.5 Bounce Time	
1.6 Free Position	7.2±0.2mm
1.7 Operating Position	6.8±0.2mm
1.8 Position Travel	
1.9 Return Force	

2.Reliable Rating

2.1 Mechanical Life	100,000 CYCLES
2.2 Electrical Life	100,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC250V
2.4 Withstand Voltage	AC600V 1 minute
2.5 Soldering Technic	Hand Soldering
2.6 Operating Temper	-20°C ~ +70°C
2.7 Ambient Humidity Used	<85%RH

Material list

NO.	PARTS	MATERIAL	Q'TY	FINISHING
8				
7				
6	Spring	SUS301	1	
5	Spring Plate	SUS301	1	
4	Terminal	C2680	2	
3	Base	Nylon	1	
2	Case	PBT	1	
1	Button	PBT	1	

Tolerance:±0.2		UNITS	mm	东莞市铀高电子制品有限公司			
		MAT'L					
		SEE NOTE		TITLE:	PART NO:		
		FINISH		TACT SWITCH	YT-05TRL-XX-W		
		SEE NOTE		DR:	Ricky 2017/7/20	DWG NO.:	
		Q'TY		CHKD:	Ricky 2017/7/20	ATD-05TRL-80G-W	
				APPD:		SCALE	SHEET
						1:1	1/1
						REV.	CUSTOMER
						A	DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.