







RoHS
Compliant
2002/95/EC

REV.	ECN. NO.	NO.	APPD.



DIMENSIONS



CIRCUIT DIAGRAM



P.C.B MOUNTING PATTERN DIMENSION



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.30±0.15mm	
Operating Force	160±50gf	250±100gf
Operating Life(cycles)	100,000	

NO.	PARTS	MATERIAL	Q'TY	FINISHING	
5	SPRING PLATE	PBS	1	Ag CALD	WITHIN 1.5mm:±0.1mm
4	TERMINAL	BRASS STRIP	1	Ag COATING	OVER 1.5mm:±0.2mm
3	CASE	NYLON+F.G	1	BLACK	
2	COVER	PET	1	NATURAL	
1	KNOB	NYLON+F.G	1	BLACK	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNO TECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNO TECH INC.

UNITS	东莞市铀高电子制品有限公司			
mm				
MAT'L				
SEE NOTE	TITLE: TACT SWITCH		PART NO.: YT-1103EA	
FINISH	DR: Ricky 2017/08/02		DWG NO.: AZJ-1103E	
SEE NOTE	CHKD: Ricky 2017/08/02			
Q'TY	APPD:		SCALE: 4:1	SHEET: 1/1
			REV.: A	CUSTOMER DRAWING