








RoHS
Compliant
2002/95/EC


| REV. | ECN. | NO. | APPD. |
|------|------|-----|-------|
| | | | |
| | | | |
| | | | |

DIMENSIONS



CIRCUIT DIAGRAM

P.C.B MOUNTING PATTERN DIMENSION



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

| | |
|------------------------|------------|
| RATING | DC12V 50mA |
| CONTACT RESISTANCE | 100mΩ MAX. |
| TRAVEL | 0.2±0.1mm |
| OPERATING FORCE | 160±50gf |
| OPERATING LIFE(cycles) | 100,000 |



| | | | | | | | | | | | | |
|-----|-------|----------|------|-----------|---------|--------|----------|-------------|------------------|-------|-----------|----------|
| 8 | | | | | .X ±0.3 | X. ±3° | UNITS | mm | 东莞市铀高电子制品有限公司 | | | |
| 7 | | | | | | | MAT'L | | | | | |
| 6 | | | | | | | SEE NOTE | TITLE: | PART NO.: | | | |
| 5 | | | | | | | | TACT SWITCH | YT-1141N | | | |
| 4 | | | | | | | FINISH | DR: | Ricky 2015/05/08 | | DWG NO.: | |
| 3 | | | | | | | SEE NOTE | CHKD: | Ricky 2015/05/08 | | AKS-1141N | |
| 2 | | | | | | | Q'TY | APPD: | SCALE | SHEET | REV. | CUSTOMER |
| 1 | | | | | | | | | 9:1 | 1/1 | A | DRAWING |
| NO. | PARTS | MATERIAL | Q'TY | FINISHING | | | | | | | | |

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.