






RoHS  
Compliant  
2002/95/EC  
Process  
Capable

REV.	ECN.	NO.	APPD.


### DIMENSIONS



### CIRCUIT DIAGRAM





### PRODUCT IMAGE



### P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



### ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.25 ± 0.1mm	
Operating Force	160±30gf	250±50gf
Operating Life(cycles)	50,000	30,000



.X ±0.2 X. ±2'  
UNITS mm  
MAT'L  
SEE NOTE  
FINISH  
SEE NOTE  
Q'TY  
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

东莞市铀高电子制品有限公司			
TITLE: TACT SWITCH	PART NO.: YT-1188		
DR: Ricky 2014/04/01	DWG NO.: ASI-1188		
CHKD: Ricky 2014/04/01	SCALE 1:1	SHEET 1/1	REV. A
APPD:	CUSTOMER DRAWING		

