






RoHS  
Compliant  
2002/95/EC


REV.	ECN. NO.	APPD.

### P.C.B MOUNTING PATTERN DIMENSION

### DIMENSIONS



### CIRCUIT DIAGRAM



### ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.3±0.15mm	
Operating Force	160±50gf	250±100gf
Operating Life(cycles)	100,000	



NO.	PART NAME	MATERIAL	QTY.	FINISHING
5	SPRING PLATE	PBS	1	Ag CLAD
4	TERMINAL	BRASS STRIP	4	Ag COATING
3	CASE	NYLON+F.G	1	BLACK
2	COVER	MILD STEEL	1	Ni COATING
1	KNOB	NYLON+F.G	1	NATURAL

WITHIN 1.5mm ±0.1	UNITS mm
OVER 1.5mm ±0.2	MAT'L
	SEE NOTE
	FINISH
	SEE NOTE
	Q'TY

<b>东莞市铀高电子制品有限公司</b>			
TITLE: TACT SWITCH		PART NO.: YT-1103SA	
DR: Ricky 2017/09/20		DWG NO.:	
CHKD: Ricky 2017/09/20		SCALE: 4:1	SHEET: 1/1
APPD:		REV. A	CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

