





RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



DIMENSIONS



CIRCUIT DIAGRAM



PRODUCT IMAGE





P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100m Ω Max.	
Travel	0.15 \pm 0.1mm	
Operating Force	160 \pm 30gf	250 \pm 50gf
Operating Life(cycles)	100,000	



.X ± 0.2 X. $\pm 2^*$

UNITS mm

MAT'L SEE NOTE

FINISH SEE NOTE

Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

东莞市铀高电子制品有限公司			
TITLE: TACT SWITCH		PART NO.: YT-1137	
DR: Ricky 2017/04/06		DWG NO.: ASI-1137	
CHKD: Ricky 2017/04/06		SCALE: 1:1	SHEET: 1/1
APPD:		REV.: A	CUSTOMER DRAWING