






RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



CIRCUIT DIAGRAM





PRODUCT IMAGE



P.C.B MOUNTING PATTERN DIMENSION


The following soldering patterns are recommended for reflow soldering



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.15 ± 0.1mm	
Operating Force	160±30gf	250±50gf
Operating Life(cycles)	100,000	



.X ±0.2	X. ±2'	UNITS	mm	东莞市铀高电子制品有限公司			
		MAT'L					
		SEE NOTE		TITLE:	PART NO.:		
				TACT SWITCH	YT-1184C		
		FINISH		DR:	2014/03/28		DWG NO.:
		SEE NOTE		Ricky	2014/03/28		ASI-1184C
		Q'TY		CHKD:	2014/03/28		SCALE
				APPD:	1:1	SHEET	REV.
					1/1	A	CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.