






RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.


DIMENSIONS



CIRCUIT DIAGRAM



PRODUCT IMAGE






MODEL CODE

YT-1187U -

	H
-	1.5
A	4.3
B	1.7
C	1.6
D	2.3
E	3.0

P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.25 ± 0.1mm	
Operating Force	160±30gf	250±50gf
Operating Life(cycles)	100,000	

.X ±0.2	X. ±2'	UNITS mm	东莞市铀高电子制品有限公司			
		MAT'L				
		SEE NOTE	TITLE: TACT SWITCH	PART NO.: YT-1187U		
		FINISH SEE NOTE	DR: Ricky 2014/03/31	DWG NO.: ASI-1187U		
		Q'TY	CHKD: Ricky 2014/03/31	SCALE	SHEET	REV.
			APPD:	1:1	1/1	A
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.</small>						CUSTOMER DRAWING