







RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.


DIMENSIONS





MODEL CODE



P.C.B LAYOUT
BOTTOM VIEW



CIRCUIT DIAGRAM



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	DC50V 0.3A
CIRCUIT	1P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	2mm
OPERATING FORCE	250±100gf
OPERATING LIFE(cycles)	10,000



8					WITHIN 1.5mm: ±0.1mm	UNITS mm	东莞市铀高电子制品有限公司				
7					OVER 1.5mm: ±0.2mm	MAT'L					
6	SPRING PLATE	PBS STRIP	1	NATURAL		SEE NOTE	TITLE:	SLIDE SWITCH / VERTICAL			PART NO.:
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED			DR:	Ricky 2015/05/19			DWG NO.:
4	TERMINAL	BRASS STRIP	3	Ag PLATED			CHKD:	Ricky 2015/05/19			SCALE SHEET REV. CUSTOMER 4:1 1/1 A DRAWING
3	BASE	PHENOLIC RESIN	1	NATURAL			APPD:				
2	FRAME	STEEL STRIP	1	Ni PLATEFD			THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.				
1	KNOB	PDM	1	BLACK							
NO.	PARTS	MATERIAL	Q'TY	FINISHING							