








RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.


DIMENSIONS



MODEL CODE



P.C.B LAYOUT
BOTTOM VIEW



CIRCUIT DIAGRAM

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.3A 50V DC
CIRCUIT	1P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	2.5mm
OPERATING FORCE	250±100gf
OPERATING LIFE(cycles)	10,000

8					WITHIN 1.5mm: ±0.1mm	UNITS	mm	东莞市铀高电子制品有限公司							
7					OVER 1.5mm: ±0.2mm	MAT'L									
6						SEE NOTE		TITLE:	SLIDE SWITCH / VERTICAL			PART NO.:	SS-12E17		
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED				DR:	Ricky 2015/05/21			DWG NO.:	ADL-12E17		
4	TERMINAL	BRASS STRIP	3	Ag PLATED				CHKD:	Ricky 2015/05/21						
3	BASE	PHENOLIC RESIN	1	NATURAL				APPD:				SCALE	SHEET	REV.	CUSTOMER
2	FRAME	STEEL STRIP	1	BLACK								4:1	1/1	A	DRAWING
1	KNOB	POM	1	BLACK											
NO.	PARTS	MATERIAL	Q'TY	FINISHING											

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

