







RoHS
Compliant
2002/95/EC

REV.	ECN. NO.	APPD.

DIMENSIONS



RECOMMENDED P.C.B. LAYOUT
UNSPECIFIED TOLERANCE:±0.05
(BOTTOM VIEW)



MODEL CODE:

DCB0-00390- A G PB BK S 0 4

- (1) (2) (3)(4) (5) (6) (7)(8) (9)
- (1):Series type:DIP DC POWER JACK.
(2):Series No.
(3):Schematic option: A , B
(4):Center pin diameter:
G=Ø1.65
(5):Material of housing:
PB=PBT (Standard)
(6):Housing color:
BK=Black(426C) 4A=Yellow(0020)
(7):Terminal plating
S=Silver(Ag)
(8):Special option:
0=Circle needle
1=Even needle
(9):Packing mode:
4=Bag packing

SPECIFICATION:

- Rating : DC 20V 2A;
- Contact resistance: ≤30mΩ;
After test:≤50mΩ
- Insulation resistance: ≥100MΩ (DC500V);
After test:≥50MΩ
- Withstand voltage: 500VAC ;
- Insertion and extraction force: 3-30N;
- life test: 5,000 cycles;
- Operation temperature range:-20°C~70°C;
- Preservative temperature range:-40°C~85°C;



DC MATE PLUG

○: ITEM NO. □: TERMINAL NO.

NO.	PARTS	MATERIAL	Q'TY	FINISHING	TOLERANCE	ANGLES	UNITS	东莞市铀高电子制品有限公司			
④	Shunt terminal ③	Brass t=0.4	1	Silver plating	±0.3	±2'	mm	东 莞 市 铀 高 电 子 制 品 有 限 公 司 TITLE: DIP DC POWER JACK PART NO.: DCB0-00390 DR: Ricky 2019/04/12 DWG NO.: AB0-00390 CHKD: Ricky 2019/04/12 APPD:			
③	Tip spring ②	Phosphor bronze t=0.3	1	Silver plating			MAT'L				
②	Center pin ①	Brass	1	Silver plating			FINISH				
①	Housing	PBT	1				Q'TY	SCALE SHEET REV. CUSTOMER 1:1 1/1 A DRAWING			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.											