








RoHS Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



P.C.B Layout
(Copper-sided view)




SECTION A-A

MODEL CODE:


- DCB0-00450- A □ LC BK S 0 1
 (1) (2) (3)(4) (5) (6) (7)(8) (9)
 (1):Series type:SMD DC POWER JACK.
 (2):Series No.
 (3):Schematic option: A,B
 (4):Center pin diameter:
 C=φ1.0, E=φ1.3
 (5):Material of housing:
 LC=LCP(Standard)
 (6):Housing color:
 BK=Black
 (7):Terminal plating:
 S=Silver(Ag),G=Gold(Au)
 (8):Special option:
 0=No special option
 (9):Packing mode:
 1=Reel packing
 3=Plastic box packing

SPECIFICATION

- Rating : DC 12V 1A;
- Contact resistance: ≤30mΩ;
- Insulation resistance: ≥100MΩ (DC500V);
- Withstand voltage: 500VAC ;
- Insertion and extraction force: 3-30N;
- life test: 5,000 cycles.
- Operation temperature range:-20°C~70°C;
- Preservative temperature range:-40°C~85°C;



Model No.	C	E
CENTER PIN	φ1.0	φ1.3



DC MATE PLUG

○: ITEM NO. □: TERMINAL NO.

⑤	Shunt terminal ③	Brass,t=0.25	1	Silver/Gold plating
④	Tip spring ②	Beryllium bronze,t=0.3	1	Silver/Gold plating
③	Center pin terminal ①	Brass,t=0.2	1	Silver/Gold plating
②	Center pin ①	Brass	1	Nickel/Gold plating
①	Housing	LCP	1	
NO.	PARTS	MATERIAL	Q'TY	FINISHING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

TOLERANCE	ANGLES	UNITS	mm	东莞市铀高电子制品有限公司 TITLE: SMD DC POWER JACK PART NO.: DCB0-00450 DR: Ricky 2018/06/20 DWG NO.: AB0-00450 CHKD: Ricky 2018/06/20 SCALE SHEET REV. CUSTOMER DRAWING 1:1 1/1 A			
±0.3	±2'	MAT'L	SEE NOTE				
		FINISH	SEE NOTE				
		Q'TY	APPD:				