








RoHS Compliant  
2002/95/EC  
Halogen Free

REV.	ECN.	NO.	APPD.



DIMENSIONS



MODEL CODE:  
DCT0-061DH3- A □ 10 BK S 0 1  
(1) (2) (3)(4)(5) (6) (7)(8) (9)  
(1):Series type:SMD DC POWER JACK.  
(2):Series No.  
(3):Schematic option: A  
(4):Center pin diameter:  
H=∅2.0mm,J=∅2.5mm  
(5):Material of housing:  
10=PA10T  
(6):Housing color:  
BK=Black  
(7):Terminal plating:  
S=Silver(Ag)  
(8):Special option:  
0=No special option  
(9):Packing mode:  
1=Reel packing



Specification:  
1.Rating : 5A/16V DC Max.  
2.Contact resistance: ≤30mΩ  
After test:≤60mΩ  
3.Insulation resistance: ≥100MΩ (DC500V).  
After test:≥50MΩ  
4.Withstanding voltage: 500VAC.  
5.Insertion and extraction force: 0.3~3Kgs.  
6.Life test: 5,000cycles min.  
7.Operation temperature range:-25℃~85℃.



RECOMMENDED P.C.B. LAYOUT  
TOLERANCE:±0.05  
(TOP VIEW)

MODEL NO.	H	J
CENTER PIN	∅2.0mm	∅2.5mm

Bill of materials:

NO.	PARTS	MATERIAL	Q'TY	FINISHING
6	CENTER PIN	COPPER	1	NICKEL PLATED
5	TERMINAL 1	BRASS	1	SILVER PLATED
4	TERMINAL 2	COPPER ALLOY	1	SILVER PLATED
3	TERMINAL 3	BRASS	1	SILVER PLATED
2	HOUSING	PA10T	1	UL94V-0
1	COVER	PA10T	1	UL94V-0

TOLERANCE	ANGLES	UNITS
±0.3	±2°	mm
		MAT'L
		SEE NOTE
		FINISH
		SEE NOTE
		Q'TY

东莞市铀高电子制品有限公司

TITLE: SMD DC POWER JACK PART NO.: DCT0-061DH3

DR: Ricky 2018/10/03 DWG NO.: AT0-061DH3

CHKD: Ricky 2018/10/03

APPD:

SCALE: 1:1 SHEET: 1/1 REV: A CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

