




RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



MODEL CODE:

DCS0-0203H- A □ PB BK I 0 3

(1) (2) (3)(4)(5) (6) (7)(8) (9)

(1):Series type:DIP DC POWER JACK.

(2):Series No.

(3):Schematic option: A

(4):Center pin diameter:

H= $\phi 2.0$ mm , J= $\phi 2.5$ mm

(5):Material of housing:

PC=PBT

(6):Housing color:

BK=Black

(7):Terminal plating

T=Tin(Sn)

(8):Special option:

0=No special option

(9):Packing mode:

3=Plastic box packing

Specification:

1.Rating : DC 24V 3.5A.

2.Contact resistance : ≤ 100 m Ω .


3.Insulation resistance : ≥ 100 M Ω (DC250V).

4.Withstanding voltage: 500VAC .


5.Insertion and extraction force: 3~30N.

6.life test: 5000cycles min.

7.Operation temperature range:-25°C~85°C



Model No.	H	J
CENTER PIN	$\phi 2.0$	$\phi 2.5$



DC MATE PLUG

Bill of materials:

NO.	PARTS	MATERIAL	Q'TY	FINISHING
6	PIN	BRASS	1	Ni-Plating
5	CURVE PIECE	BRASS	1	Sn-Plating
4	FLAT PIECE	BRASS	1	Sn-Plating
3	SPRING	PBS	1	Sn-Plating
2	COVER	PBT	1	
1	HOUSING	PBT	1	

TOLERANCE	ANGLES	UNITS
.X ± 0.3	X° $\pm 5^\circ$	mm
.XX ± 0.2	.X° $\pm 3^\circ$	MAT'L
.XXX ± 0.1		SEE NOTE
		FINISH
		SEE NOTE
		Q'TY

东莞市铀高电子制品有限公司			
TITLE: DIP DC POWER JACK		PART NO.: DCS0-0203H	
DR: Ricky 2019/03/26		DWG NO.: ASS-0203H	
CHKD: Ricky 2019/03/26		SCALE: 1:1	SHEET: 1/1
APPD:		REV: A	CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

