Pb Process Capable

RoHS Compliant 2002/95/EC

REV.	ECN. NO.	APPD.

DIMENSIONS





RECOMMENDED P.C.B. LAYOUT
UNSPECIFIED TOLERANCE:±0.05
(TOP VIEW)

MODEL CODE:

DCB0-025BM- A □ PB BK C 0 4
(1) (2) (3)(4) (5) (6) (7)(8) (9)

(1):Series type:DIP DC POWER JACK.
(2):Series No.
(3):Schematic option: A , B
(4):Center pin diameter:
H=ø2.0 , I=ø2.35 , J=ø2.5
(5):Material of housing:
PB=PBT (Only)
(6):Housing color:
BK=Black (Only)
(7):Terminal plating
S=Silver(Ag)
T=Tin(Sn)
C=copper&tin alloy plating (Standard)
(8):Special option:
0=No special option
(9):Packing mode:
4=Bag packing

SPECIFICATION:
1.Rating : DC 30V 3A;
2.Contact resistance: ≤30mΩ;
After test:≤50mΩ
3.Insulation resistance: ≥100MΩ (DC500V);
After test:≥50MΩ
4.Withstand voltage: 500VAC ;
5.Insertion and extraction force: 3-30N;
6.life test: 5,000 cycles;
7.Operation temperature range:-20°C~70°C;
8.Preservative temperature range:-40°C~85°C;





Nut



Washer

东莞市铀高电子制品有限公司
正版认证
受控文件



CIRCUIT DIAGRAM



DC MATE PLUG

Model No.	H	I	J
CENTER PIN	ø2.0	ø2.35	ø2.5

◯: ITEM NO. □: TERMINAL NO.

NO.	PARTS	MATERIAL	Q'TY	FINISHING
⑨	Washer	Stel	1	Ni-plating
⑧	Nut	Brass	1	Ni-plating
⑦	Washer	Bakelite	2	
⑥	Pin	Bronze	1	Ni-plating
⑤	Bushing	Brass	1	Ni-plating
④	Shunt Terminal 4	Brass	1	Cu-Sn-Plating
③	Tip Spring 2	Phosphor bronze	1	Cu-Sn-Plating
②	Center pin terminal 1	Brass	1	Cu-Sn-Plating
①	Housing	PBT	1	Black

TOLERANCE	ANGLES
±0.3	±2°

UNITS mm
MAT'L SEE NOTE
FINISH SEE NOTE
Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

东莞市铀高电子制品有限公司

TITLE: DIP DC POWER JACK
PART NO.: DCB0-025BM
DR: Ricky 2019/04/10
DWG NO.: AB0-025BM
CHKD: Ricky 2019/04/10
APPD:

SCALE	SHEET	REV.	CUSTOMER DRAWING
1:1	1/1	A	