







RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



P.C.B LAYOUT



MODEL CODE:

DCE0-02290- A □ PC BK S 0 4

(1) (2) (3)(4) (5) (6) (7)(8) (9)

(1):Series type:DIP DC POWER JACK.

(2):Series No.

(3):Schematic option: A

(4):Center pin diameter:

H=φ2.0 , I=φ2.35 , J=φ2.5, X=φ2.7

(5):Material of housing:

PC=PC

(6):Housing color:

BK=Black

(7):Terminal plating

S=Silver(Ag)

(8):Special option:

0=No special option

(9):Packing mode:

4=Bag packing

Specification:

1.Rating :DC 30V 0.3A.

2.Contact resistance :≤100mΩ.



3.Insulation resistance : ≥100MΩ (500VDC).

4.Withstanding voltage: 500VAC .

5.Insertion and extraction force: 0.3~3Kgs.

6.life test: 5000cycles min.

7.□peration temperature range:-25°C~85°C



DC MATE PLUG

Model No.	H	I	J	X
CENTER PIN	φ2.0	φ2.35	φ2.5	φ2.7

Bill of materials:

NO.	PARTS	MATERIAL	Q'TY	FINISHING
6	TERMINAL	BRASS STRIP	1	Ag PLATED
5	TERMINAL	BRASS STRIP	1	Ag PLATED
4	SPRING TERMINAL	PBS	1	Ag PLATED
3	TERMINAL BASE	PHENOLIC RESIN	1	NATURAL
2	PLUG PIN	BRASS	1	Ag PLATED
1	CASE	PC	1	BLACK/WHITE

GENERAL TOLERANCE  
WITHIN 1.5mm±0.1mm  
OVER 1.5mm±0.2mm

UNITS mm

MAT'L  
SEE NOTE

FINISH  
SEE NOTE

Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

**东莞市铀高电子制品有限公司**

TITLE: DIP DC POWER JACK PART NO.: DCE0-02290

DR: Ricky 2019/03/19 DWG NO.: AZJ-02290

CHKD: Ricky 2019/03/19

APPD:

SCALE	SHEET	REV.	CUSTOMER
1:1	1/1	A	DRAWING