








RoHS
Compliant
2002/95/EC

Halogen Free

DIMENSIONS



RECOMMENDED P.C.B. LAYOUT
TOLERANCE: ±0.05
(TOP VIEW)



MODEL CODE:

DCT0-034DH2- A □ 10 BK S 0 1
(1) (2) (3)<(4)<(5) (6) (7)<(8) (9)

(1):Series type:SMD DC POWER JACK.

(2):Series No.

(3):Schematic option: A

(4):Center pin diameter:
H=ø2.0mm,J=ø2.5mm

(5):Material of housing:
10=PA10T

(6):Housing color:
BK=Black

(7):Terminal plating:
S=Silver(Ag)

(8):Special option:
0=No special option

(9):Packing mode:
1=Reel packing

Specification:

1.Rating : 5A/16V DC Max.

2.Contact resistance: ≤30mΩ
After test:≤60mΩ


3.Insulation resistance: ≥100MΩ (DC500V).
After test:≥50MΩ

4.Withstanding voltage: 500VAC.


5.Insertion and extraction force: 0.3~3Kgs..

6.Life test: 5,000cycles min.

7.Operation temperature range:-25℃~85℃.



CIRCUIT DIAGRAM



DC MATE PLUG

MODEL NO.	H	J
CENTER PIN	ø2.0mm	ø2.5mm

Bill of materials:

NO.	PARTS	MATERIAL	Q'TY	FINISHING	TOLERANCE	ANGLES	UNITS
6	CENTER PIN	COPPER	1	NICKEL PLATED	±0.3	±2°	mm
5	TERMINAL 1	BRASS	1	SILVER PLATED			MAT'L
4	TERMINAL 2	COPPER ALLOY	1	SILVER PLATED			SEE NOTE
3	TERMINAL 3	BRASS	1	SILVER PLATED			FINISH
2	HOUSING	PA10T	1	UL94V-0			SEE NOTE
1	COVER	PA10T	1	UL94V-0			Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOVATECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOVATECH INC.

UNITS				mm			
MATERIAL				SEE NOTE			
FINISH				SEE NOTE			
Q'TY				APPD:			
<p>东莞市铀高电子制品有限公司</p>				TITLE:		PART NO.:	
				SMD DC POWER JACK		DCT0-034DH2	
<p>DR: Ricky 2018/10/01</p>				DWG NO.:		AT0-034DH2	
				SCALE		SHEET	
<p>CHKD: Ricky 2018/10/01</p>				1:1		1/1	
				A		CUSTOMER DRAWING	