



RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.








A

B

C

D


E



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 1AMP,30V AC;
 - INSULATION RESISTANCE: 100MΩ MIN;
 - CONTACT RESISTANCE: 50mΩ MAX;
 - WITHSTANDING VOLTAGE: 300V AC;
 - OPERATING TEMPERATURE:-55°C TO +85°C.
- Mechanical:
 - Mating Force: 30N MAX
 - Unmating Force: 7N MIN.
- DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.



Bill of materials:

4	HOUSING	LCP	1	UL94V-0
3	OUTSIDE SHELL	COPPER ALLOY	1	PLATED NICKEL
2	INNER SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	9	PLATED GOLD
NO	PARTS	MATERIAL	QTY	FINISHING

X. ±0.35	X.' ±2°	UNITS	mm
.X ±0.3	.X' ±1°	MAT'L	SEE NOTE
.XX ±0.25	.XX'	FINISH	SEE NOTE
.XXX ±0.15	.XXX'	Q'TY	SEE NOTE

东莞市铀高电子制品有限公司			
TITLE: IEEE 1394 9P/F SMT(平脚)		PART NO.: IENF-092N-4BH82	
DR: gan 2012/07/02		DWG NO.: AII-H82	
CHKD: gan 2012/07/02		SCALE: 1:1	SHEET: 1/1
APPD:		REV.: B	CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNTECH INC.

