









RoHS
Compliant
2002/95/EC

Halogen Free

REV.	ECN. NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

1. ELECTRICAL:

- VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX / PIN2&3&4 1AMP MAX., 30V AC;
- INSULATION RESISTANCE: 100MΩ MIN;
- CONTACT RESISTANCE: 30mΩ MAX;
- WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
- OPERATING TEMPERATURE: -30°C TO +80°C.

Mechanical:

- Mating Force: 35N MAX
- Unmating Force: 10N MIN.

- DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.



4.PART NO.

MUYF-05*T-4BHUA233

1:Au 1U*
6:Au 30U*

T:TIN
N:NICKEL

W:WHITE
B:BLACK

1:PBT
2:PA6T
3:PA9T
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市铀高电子制品有限公司			
3	SHELL	COPPER ALLOY	1	PLATED TIN	X. ±0.35	X.* ±2*	TITLE: MICRO USB B TYPE F 5P SMT破板式1.6 四只脚 PART NO.: MUYF-05XT-4BHUA233 DR: Ricky 2018/9/7 DWG NO.: AII-HUA233 CHKD: Ricky 2018/9/7 APPD:	SCALE: 5:1 SHEET: 1/1 REV: A CUSTOMER DRAWING		
2	HOUSING	LCP+30%GF	1	UL94V-0	.X ±0.30	.X* ±1*				
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XX ±0.25	.XX*				
					.XXX ±0.15	.XXX*				
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC					
					Q'TY					