








RoHS  
Compliant  
2002/95/EC

Halogen Free

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT  
TOLERANCE: ±0.03



NOTES:

1.ELECTRICAL:


- 1)VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX
- 2) PIN2&3&4 1AMP MAX. ,30V AC;
- 3)INSULATION RESISTANCE: 100MΩ MIN;
- 4)CONTACT RESISTANCE: 30mΩ MAX;
- 5)WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
- 6)OPERATING TEMPERATURE: -30°C TO +80°C.

2.Mechanical:

- 1)Mating Force: 35N MAX
  - 2)Unmating Force: 10N MIN.
- 3.DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

MUYF-05\*T-4BHUA537



Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市铀高电子制品有限公司				
3	SHELL	COPPER ALLOY	1	PLATED TIN	X. ±0.35	X.' ±2'	MAT'L	TITLE: MICRO USB B TYPE F 5P SMT沉板0.9 平口端子加长0.3		PART NO.: MUYF-05*T-4BHUA537	
2	HOUSING	LCP+30%GF	1	UL94V-0	.X ±0.30	.X' ±1'	SEE NOTE	DR: Ricky 2018/5/3		DWG NO.: AII-HUA537	
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XX ±0.25	.XX'	FINISH	CHKD: Ricky 2018/5/3		SCALE SHEET REV. CUSTOMER 5:1 1/1 A DRAWING	
					.XXX ±0.15	.XXX'	SEE NOTE	APPD:			
<p>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNTECH INC</p>							Q'TY				