









RoHS
Compliant
2002/95/EC

Halogen Free

REV.	ECN. NO.	APPD.



NOTES:

1.ELECTRICAL:

- 1)VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX / PIN2&3&4 1AMP MAX. ,30V AC;
- 2)INSULATION RESISTANCE: 100MΩ MIN;
- 3)CONTACT RESISTANCE: 30mΩ MAX;
- 4)WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
- 5)OPERATING TEMPERATURE: -30°C TO +80°C.

2.Mechanical:

- 1)Mating Force: 35N MAX
- 2)Unmating Force: 10N MIN.
- 3.DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

MUYF-05*T-4BHUA576

1: Au 1U"	W: WHITE
6: Au 30U"	B: BLACK
T: TIN	1: PBT
N: NICKEL	2: PA6T
	3: PA9T
	4: LCP



Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市铀高电子制品有限公司							
3	SHELL	COPPER ALLOY	1	PLATED TIN	X. ±0.35	X.* ±2*	SEE NOTE	TITLE: MICRO USB B TYPE F 5P SMT沉板0.9 长6.8有导位		PART NO.: MUYF-05*T-4BHUA576				
2	HOUSING	LCP+30%.GF	1	UL94V-0	.X ±0.30	.X* ±1*						DR: Ricky 2018/5/4	DWG NO.: AII-HUA576	
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XX ±0.25	.XX*						CHKD: Ricky 2018/5/4		
					.XXX ±0.15	.XXX*	APPD:	SCALE: 5:1	SHEET: 1/1	REV: A	CUSTOMER DRAWING			

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INDDTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INDDTECH INC

