










RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

- 1) ELECTRICAL:
 1) VOLTAGE CURRENT RATING: 1.0AMP,100V AC;
 2) INSULATION RESISTANCE: 100MΩ MIN;
 3) CONTACT RESISTANCE: 50mΩ MAX;
 4) WITHSTANDING VOLTAGE: 100V AC;
 5) OPERATING TEMPERATURE:-30°C TO +80°C.
2. Mechanical:
 1) Mating Force: 35N MAX
 2) Unmating Force: 7N MIN.
3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

MUNF-101T-4BVS14-M

- 1:Au 1U"
- 2:PA6T
- 3:PA9T
- 4:LCP

Bill of materials:

3	HOUSING	LCP+30%GF	1	UL94V-0
2	SHELL	STAINLESS STEEL	1	PLATED TIN
1	TERMINAL	COPPER ALLOY	10	PLATED GOLD/TIN
NO	PARTS	MATERIAL	QTY	FINISHING

X. ±0.35	X.' ±2'	UNITS	mm
.X ±0.3	.X' ±1'	MAT'L	SEE NOTE
.XX ±0.25	.XX'	FINISH	SEE NOTE
.XXX ±0.15	.XXX'	Q'TY	SEE NOTE

东莞市铀高电子制品有限公司

TITLE: MINI USB 10PIN PHILIPS 母座
AB TYPE有柱

PART NO.: MUNF-101T-4BVS14-M

DR: gan 2014/06/21

CHKD: gan 2014/06/21

APPD:

DWG NO.: AII-VS14-M

SCALE: 1:1 SHEET: 1/1 REV.: B CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.