










RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:
1. ELECTRICAL:
1) VOLTAGE CURRENT RATING: 2AMP, 30V AC;
2) INSULATION RESISTANCE: 1000MΩ MIN;
3) CONTACT RESISTANCE: 30mΩ MAX;
4) WITHSTANDING VOLTAGE: 500V AC;
5) OPERATING TEMPERATURE: -55°C TO +85°C.
2. Mechanical:
1) Mating Force: 35N MAX
2) Unmating Force: 10N MIN.
3. NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-04*N-1*P63

1-Au 1U*
6-Au 30U*
1-PBT
2-PA6T
3-PA9T
4-LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X.	X.*	UNITS	东莞市铀高电子制品有限公司						
4	COVER	PBT	1	UL94V-0	±0.35	±2*	mm	TITLE:		PART NO.:				
3	HOUSING	PBT	1	UL94V-0	±0.3	±1*	MAT'L	USB AF 180° DIP 14.5mm 弯脚		USAF-04*N-1*P63				
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	±0.25	*	SEE NOTE	DR: gan 2012/6/29		DWG NO.:				
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	±0.15	*	SEE NOTE	CHKD: gan 2012/6/29		AII-P63				
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.								Q'TY	APPD:		SCALE	SHEET	REV.	CUSTOMER DRAWING
								1:1	1/1	B				