









RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:

1) ELECTRICAL:

- VOLTAGE CURRENT RATING: 2AMP, 30V AC;
- INSULATION RESISTANCE: 1000MΩ, MIN;
- CONTACT RESISTANCE: 30mΩ MAX;
- WITHSTANDING VOLTAGE: 500V AC;
- OPERATING TEMPERATURE: -55°C TO +85°C.

2) Mechanical:

- Mating Force: 35N MAX
- Unmating Force: 10N MIN.

3) NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-04\*N-1\*P67

1: Au 1U\*  
6: Au 30U\*

W: WHITE  
B: BLACK

1: PBT  
2: PA6T  
3: PA9T  
4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	UNITS	东莞市铀高电子制品有限公司				
3	HOUSING	PBT+30%GF	1	UL94V-0	X. ±0.35	X.' ±2*	mm	TITLE: USB A/F全包直脚插板式(13.7)		PART NO.: USAF-04*N-1*P67	
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.X ±0.30	.X' ±1*	MAT'L				
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XX ±0.25	.XX*	SEE NOTE	CHKD: gan 2012/6/30		SCALE: 1:1 SHEET: 1/1 REV: B	
					.XXX ±0.15	.XXX*	FINISH				
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.		Q'TY				

