



1. ELECTRICAL:
- VOLTAGE CURRENT RATING: 2.0AMP,30V AC;
 - INSULATION RESISTANCE: 1000 Ω MIN;
 - CONTACT RESISTANCE: 30m Ω MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE:-55°C TO +85°C.
2. Mechanical:
- Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04*N-1*PA0

1:Au 1U"
6:Au 30U"

1:PBT
2:PA6T
3:PA9T
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm
4	COVER	PBT	1	UL94V-0	X. \pm 0.35	X.' \pm 2'
3	HOUSING	PBT	1	UL94V-0	.X \pm 0.3	.X' \pm 1'
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XX \pm 0.25	.XX'
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX \pm 0.15	.XXX'

东莞市铨高电子制品有限公司

TITLE: USB A/F 180° DIP (15.00)	PART NO.: USAF-04*N-1*PA0
DR: gan 2012/7/05	DWG NO.: AII-PA0
CHKD: gan 2012/7/05	SCALE SHEET REV. CUSTOMER 1:1 1/1 B DRAWING
APPD:	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECHING AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC

