



RoHS Compliant
 2002/95/EC
 Process Capable

REV	LTR	DESCRIPTION



- NOTES:
- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30V DC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
 - Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
 - NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO. USAF-08*N-1*R601

1: Au 1U*
 6: Au 30U*

W: WHITE
 B: BLACK
 1: PBT
 2: PA6T
 3: PA9T
 4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
5	CLIP	COPPER ALLOY	1	PLATED NICKEL
4	BACK COVER	SPCC	1	PLATED NICKEL
3	HOUSING	PBT+30%GF	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	8	PLATED GOLD/TIN

X. ±0.35	X.' ±2*	UNITS mm	东莞市铀高电子制品有限公司				
.X ±0.3	.X' ±1*	MAT'L					
.XX ±0.25	.XX*	SEE NOTE	TITLE: USB AF 双层半包直脚长胶平弹	PART NO.: USAF-08*N-1*R601			
.XXX ±0.15	.XXX*	FINISH	DR: gan 2013/12/5	DWG NO.: AII-R601			
SEE NOTE			CHKD: gan 2013/12/5	SCALE: 1:1	SHEET: 1/1	REV. B	CUSTOMER DRAWING
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC			Q'TY	APPD:			