









RoHS
Compliant
2002/95/EC

REV	LTR	DESCRIPTION	DATE	REVISER	APPD



1. ELECTRICAL:
 1) VOLTAGE CURRENT RATING: 2AMP, 30V AC;
 2) INSULATION RESISTANCE: 1000MΩ, MIN;
 3) CONTACT RESISTANCE: 30mΩ MAX;
 4) WITHSTANDING VOLTAGE: 500V AC;
 5) OPERATING TEMPERATURE: -55°C TO +85°C.
2. Mechanical:
 1) Mating Force: 35N MAX
 2) Unmating Force: 10N MIN.
3. NOTE: 1. DIMENSIONS MARKED " " TO BE CHECKED BY Q.C & IPQC.

4. PART NO.
 USAF-04*N-1*R613

1: Au 1U"
 6: Au 30U"

W: WHITE
 B: BLACK

1: PBT
 2: PA6T
 3: PA9T
 4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
3	HOUSING	PBT	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN

UNITS mm				东莞市铀高电子制品有限公司			
MAT'L							
SEE NOTE				TITLE: USB AF DIP 90° (10.0)无卷边		PART NO.: USAF-04*N-1*R613	
FINISH				DR: gan 2013/4/12		DWG NO.: AII-R613	
SEE NOTE				CHKD: gan 2013/4/12		SCALE SHEET REV. CUSTOMER DRAWING	
Q'TY				APPD:		1:1 1/1 B	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

