








RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



CIRCUIT DIAGRAM

MODEL CODE

ATI-008-MW16-1MN**-BS
1 234 5678 9

- Series Number
- Terminal Type: M=SMT
- Stem Color: W=White B=Black
- Operating Force: 16=160gf 25=250gf
- Circuit
- LED Type: M=SMT
- LED Brightness: N=Normal S=Super Bright H=Super High Bright
- LED Color: 01=Red 02=Yellow 03=Green 04=Blue 05=White 06=Pure Green 08=Amber 09=Blue Green 0A=Pink 0B=Purple
- Packing Type: BS=Blister Packing TR=Tape Reel Packing

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	DC 12V 50mA	
CONTACT RESISTANCE	100mΩ MAX.	
TRAVEL	0.25±0.1mm	
OPERATING FORCE	160±50gf	250±50gf
OPERATING LIFE(cycles)	100,000	



8							
7							
6							
5	LED		1				
4	CONTACT	PBS C5210R-EH	1	Ag CLAD			
3	TERMINAL	BRASS STRIP	4	Ag PLATED			
2	CASE	NYLON+F.G	1	BLACK			
1	KNOB	NYLON+F.G	1	NATURAL/BLACK			
NO.	PARTS	MATERIAL	Q'TY	FINISHING			

WITHIN 1.5mm: ±0.1mm	UNITS	mm			
OVER 1.5mm: ±0.2mm	MAT'L				
	SEE NOTE				
	FINISH				
	SEE NOTE				
	Q'TY				
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.</small>		东莞市铀高电子制品有限公司		YTI-008-D	
		TITLE: ILLUMINATED TACT SWITCH		PART NO.: AZJ-008-M	
		DR: Ricky 2016/10/07		DWG NO.:	
		CHKD: Ricky 2016/10/07		SCALE	SHEET
		4:1	1/1	A	