






RoHS  
Compliant  
2002/95/EC

REV.	ECN. NO.	APPD.




### DIMENSIONS



### MODEL CODE

ATI-003-DW16-4DN\*\*-BS  
1 234 5678 9

- Series Number
- Terminal Type: D=Dip
- Stem Color: W=White B=Black
- Operating Force: 16=160gf 25=250gf
- Circuit
- LED Type: D=Dip
- LED Brightness: N=Normal S=Super Bright H=Super High Bright
- LED Color: 01=Red 02=Yellow 03=Green 04=Blue 05=White 06=Pure Green 08=Amber 09=Blue Green 0A=Pink 0B=Purple 12=Red/Yellow 13=Red/Green 14=Red/Blue 23=Yellow/Green 48=Blue/Amber 58=White/Amber
- Packing Type: BS=Blister Packing



P.C.B LAYOUT  
TOP VIEW

### ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	DC 12V 50mA
CONTACT RESISTANCE	100mΩ MAX.
TRAVEL	0.25±0.1mm
OPERATING FORCE	160±50gf 250±50gf
OPERATING LIFE(cycles)	100,000

8					
7					
6	LED		1		
5	COVER	PET	1	NATURAL	
4	CONTACT	PBS C5210R-EH	1	Ag PLATED	
3	TERMINAL	BRASS STRIP	4	Ag PLATED	
2	CASE	NYLON+F.G	1	BLACK	
1	KNOB	NYLON+F.G	1	WHITE/BLACK	
NO.	PARTS	MATERIAL	Q'TY	FINISHING	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOVATECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOVATECH INC.

WITHIN 1.5mm: ±0.1mm	UNITS mm	东莞市铀高电子制品有限公司			
OVER 1.5mm: ±0.2mm	MAT'L				
SEE NOTE	FINISH	TITLE: ILLUMINATED TACT SWITCH	PART NO.: YTI-003-D		
SEE NOTE	Q'TY	DR: Ricky 2016/10/05	DWG NO.: AZJ-003-D		
		CHKD: Ricky 2016/10/05	SCALE: 4:1	SHEET: 1/1	REV. A
		APPD:	CUSTOMER DRAWING		