



□: TERMINAL NO.

Ordering information:

PJ-201M-C □□ OA T □□ 4
(1) (2) (3) (4) (5) (6) (7)

- (1): Series No
- (2): Schematic option: C
- (3): Material of housing:
AB=ABS
PB=PBT(Standard)
- (4): Housing color:
OA=Black (Standard)
Zero=Red
3_=Orange
4_=Yellow
- (5): Terminal plating
6_=Blue(Sn)(Standard)
8=Silver(Ag)
- (6) Special option
OV=Bushing is Nickel plating (Standard)
OG=Bushing is Gold plating
- (7) Packing mode: Cu&Tin Plating
4=Bag packing



SPCIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: <30mΩ;
3. Insulation resistance: >100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-25N;
6. life test: 5,000 cycles.

DSND		DATE		SCALE: N/A	MODEL TYPE: 2.5 PHONE JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm	DWG NO.:
APPD		DATE		SIZE: A4	
UNSPECIFIED TOLERANCES					WEIGHT 1.0g
东莞市铀高电子制品有限公司					SHEET 1/1
					REVISION A0

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
△X					X.X	±0.2mm
△X					X.XX	±0.1mm
△X					X.XXX	±0.05mm
REVISIONS						