



PCB LAYOUT

版本 REV	编号 ECN NO.	位置 LOCATIONS	变更内容 DESCRIPTION	日期 DATE	变更人 DESIGN
A0					

### Specifications

1. Current Rating: 1Amps
2. Insulation Resistance: 1000 MΩ min.
3. Dielectric withstanding Voltage: AC 500V
4. Contact Resistance: 30 mΩ max.
5. Operating Temperature: -25°C to +85°C
6. Contact Material: Brass
7. Insulation Material: As follows
8. Plated: As follows

### Ordering Information



东莞市铂高电子有限公司

TOLERANCE UNLESS OTHERWISE SPECIFIED		OTHERWISE SPECIFIED	
LINER	ANGLES	LINER	ANGLES
.0	±0.3	0°	±2.0°
.00	±0.2	0°	±1.0°
.000	±0.1	.00°	±0.5°

  

品名 TITLE:	料号 (P/N):	料号 (M/N):	比例 (SCALE):
PH2.0 SMT双排排针			1:1

  

制图 (DN):	审核 (CHKD):	核准 (APPD):	日期 (Date):
			09.08.19

  

单位 (UNIT):	数量 (QTY):	比例 (SCALE):	日期 (Date):
mm	XORFX	A4	