







RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



P.C.B LAYOUT
BOTTOM VIEW



CIRCUIT DIAGRAM

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	DC30V 0.1A	
CIRCUIT	2P2T	
CONTACT RESISTANCE	50mΩ MAX.	
TIMING	NON-SHORTING	
OPERATING MODE	SELF-LOCK	AP-2215L
	NON-LOCK	AP-2215N
STROKE	FULL 2.5mm	LOCK 1.5mm
OPERATING FORCE	200±100gf	
OPERATING LIFE(cycles)	10,000	



6	SPRING	SEE SPRING CHART	1	NATURAL	WITHIN 1.5mm: ±0.1mm
5	CONTACT	PBS C5210R-EH	2	Ag CLAD	OVER 1.5mm: ±0.2mm
4	CAM STICK	SUS WIRE	1	WASHING	
3	CASE	PBT 3310/BRASS STRIP	1	BLACK/Ag PLATED OVER NI PLATED	
2	COVER	POM	1	WHITE	
1	KNOB	POM	1	BLUE	
NO	PARTS	MATERIAL	QTY	FINISHING	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

UNITS	mm
MAT'L	SEE NOTE
FINISH	SEE NOTE
Q'TY	

东莞市铀高电子制品有限公司

TITLE:	PUSH SWITCH / VERTICAL		PART NO.:	AP-2215L & AP-2215N	
DR:	Ricky 2014/05/06		DWG NO.:	ADJ-2215	
CHKD:	Ricky 2014/05/06		SCALE	4:1	SHEET 1/1
APPD:			REV.	A	CUSTOMER DRAWING