



SECTION A-A

Rating :  
 5A 250V AC T105 UL cUL  
 2.5A 250V AC VDE 3C KC  
 Insert And Extract Force: 1.36kgf~6.8kgf  
 Terminal Strength:  $\geq 80N$   
 Operating Life:  $\geq 5000$  cycles  
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min  
 terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current : 1mA  
 Insulation Resistance:  $\geq 100M\Omega$  500V DC



A4				普通公差	东莞市铀高电子制品有限公司							
A3				COMMON TOLERANCE								
A2				UP TO 5	$\pm 0.20$	单位	mm	投影	品名	Ac Inlet C6型	比例	Free
A1				ABOVE 5 TO 30	$\pm 0.30$	UNIT		PROJECTED	PRODUCT NAME		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR DIMENSIONS	$\pm 0.50$	绘图	吴瑜	核对	型号	YG-6-4VS2S8(G)		
				DATE	2009.06.17	日期	2009.06.17	核准	图号	64VS2S8(G)		
						DATE		BY	DWG NO.			

东莞市铀高电子制品有限公司