



卡位内部加筋

Rating : 15A 250V AC T105 UL cUL
10A 250V AC VDE 3C KC

Insert And Extract Force: 1.36kgf~6.8kgf

Terminal Strength: $\geq 80N$

Operating Life: ≥ 5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min
terminals to Base:3750V AC (50-60Hz)1min

Leakage Current : 1mA

Insulation Resistance: $\geq 100M\Omega$ 500V DC

| | | | | | | | | | | | | |
|------|------------|----------------------|--------------------|---------------|---------------|--|----|-------------|-----|---------------|--------------|------|
| A4 | | | | 普通公差 | | 东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd | | | | | | |
| A3 | | | COMMON TOLERANCE : | 单位 | | mm | 投影 | | 品名 | Ac Inlet C14型 | 比例 | Free |
| A2 | | | UP TO 5 | ± 0.20 | | 绘图 | 吴瑜 | 核对 | 吴路方 | 型号 | 3K-14-F5 (2) | |
| A1 | 2011.12.20 | 将原19.2mm尺寸变更为19.5mm | ▲ | ABOVE 5 TO 30 | | ± 0.30 | 日期 | 2011.12.20 | 核准 | 周培雷 | 图号 | 145F |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ANGULAR | $\pm 5^\circ$ | DATE | | APPROVAL BY | | DWG NO. | | |

