



PANEL CUT-OUT

Rating :  
 5A 250V AC T105 UL cUL  
 2.5A 250V AC VDE 3C KC  
 Insert And Extract Force: 1.36kgf~6.8kgf  
 Terminal Strength: ≥80N  
 Operating Life: ≥5000 cycles  
 Withstand Voltage between all terminals: 2500VAC (50-60Hz) 1min  
 terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current : 1mA  
 Insulation Resistance: ≥100MΩ 500V DC



|      |      |                      |       |                    |               |      |    |             |              |                 |         |
|------|------|----------------------|-------|--------------------|---------------|------|----|-------------|--------------|-----------------|---------|
| A4   |      |                      |       | 普通公差               | 东莞市铀高电子制品有限公司 |      |    |             |              |                 |         |
| A3   |      |                      |       | COMMON TOLERANCE : |               |      |    |             |              |                 |         |
| A2   |      |                      |       | UP TO 5            | ±0.20         | UNIT | mm | 投影          | Ac Inlet C8型 | 比例              | Free    |
| A1   |      |                      |       | ABOVE 5 TO 30      | ±0.30         | 绘图   |    | 核校          |              |                 |         |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ANGULAR            | ±5°           | 日期   |    | 核准          | 品名           | 型号              | 图号      |
|      |      |                      |       |                    |               | DATE |    | APPROVAL BY | Ac Inlet C8型 | YG-8-17VS2B (2) | 817VS2B |