



<p>Rating :  <b>15A 250V AC</b>  <b>10A 250V AC</b>          Fuse : <b>250VAC 6.3A 2.5W</b>          Insert And Extract Force: 36kgf~6.8kgf</p> <p>Terminal Strength:  <math>\geq 80N</math>          Operating Life: <math>\geq 5000</math> cycles</p> <p>Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min          terminals to Base: 3750V AC (50-60Hz) 1min          Leakage Current :          ImA</p> <p>Insulation Resistance: <math>\geq 100M\Omega</math> 500V DC</p>	<p>器具插座</p>	<p>器具开关</p> <p>Rating:          CQC 6A 250V          10A 125V A. / <math>\sqrt{2}</math> 250V AC          VDE 6(4)A 250V V. TS5/55          IEC 6(4)A 250V</p> <p>Circuit Diagram: 4P ON-OFF</p> <p>Terminal Strength: <math>\geq 80N</math>          Electrical life: <math>\geq 10000</math> cycles</p> <p>Withstand Voltage: Withstand Voltage: 1800VAC 1min          Terminals to Button: 3000VAC 1min</p> <p>Leakage Current: ImA          Current resistance: <math>\leq 50m\Omega</math> (initial)          Insulation resistance: <math>\geq 100M\Omega</math></p>
--	-------------	--

A4				普通公差	东莞市铀高电子制品有限公司								
A3				COMMON TOLERANCE :									
A2				UP TO 5	$\pm 0.20$	单位	mm	投影		品名	Ac Inlet C14型	比例	Free
A1				ABOVE 5 TO 30	$\pm 0.30$	UNIT		核校		型号	Y6-14-5F(1.5)+RS601D1-2010011BB-3A		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	$\pm 0.50$	绘图	吴瑜	CHECKED BY		图号			
				ANGULAR	$\pm 5^\circ$	日期	2012.02.10	核准		图号	145FRS601D2010011BB-3A		
								APPROVAL BY		DRG NO.			