



Rating : 15A 250V AC
 10A 250V AC
 Fuse : 250VAC 6.3A 2.5W
 Insert And Extract Force: 1.36kgf~6.8kgf
 Terminal Strength: $\geq 80N$
 Operating Life: ≥ 5000 cycles
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
 terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current : 1mA
 Insulation Resistance: $\geq 100M\Omega$
 500V DC

Rating : 10A 250V AC
 6(4)A 250V AC
 6A 250V AC
 Terminal Strength: $\geq 80N$
 Operating Life: 1×10^4 cycles
 Withstand Voltage: Between all terminals: 1000VAC 5S
 terminals to Button: 3800VAC 5S
 Leakage Current : 1mA
 Insulation Resistance: $\geq 100M\Omega$
 Contact resistance: $\leq 20m\Omega$

A4				普通公差	东莞市铀高电子制品有限公司						
A3				COMMON TOLERANCE :							
A2				UP TO 5	±0.20	单位	mm	投影	Ac Inlet C14型	比例	Free
A1				ABOVE 5 TO 30	±0.30	UNIT		PROJECTED	SCALE		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	绘图	吴瑜	核对	品名	YG-14-2F+RS601A-10111BB	
				ANGULAR	±5°	日期	2009.06.24	核准	型号		
						DATE		APPROVAL BY	图号	142FRS601A10111BB	
									DRG NO.		