



Rating :  
15A 250V AC  
10A 250V AC

Insert And Extract Force: 1.36kgf-6.8kgf

Terminal Strength:  $\geq 80N$

Operating Life:  $\geq 5000$  cycles

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min

terminals to Base: 3750V AC (50-60Hz) 1min

Leakage Current : 1mA

Insulation Resistance:  $\geq 100M\Omega$  500V DC



|      |      |                      |       |                    |               |               |            |             |     |              |               |              |      |
|------|------|----------------------|-------|--------------------|---------------|---------------|------------|-------------|-----|--------------|---------------|--------------|------|
| A4   |      |                      |       | 普通公差               |               | 东莞市铀高电子制品有限公司 |            |             |     |              |               |              |      |
| A3   |      |                      |       | COMMON TOLERANCE : |               |               |            |             |     |              |               |              |      |
| A2   |      |                      |       | UP TO 5            | $\pm 0.20$    | 单位            | mm         | 投影          |     | 品名           | Ac Inlet C14型 | 比例           | Free |
| A1   |      |                      |       | ABOVE 5 TO 30      | $\pm 0.30$    | UNIT          |            | PROJECTED   |     | PRODUCT NAME |               |              |      |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ABOVE 30           | $\pm 0.50$    | 绘图            | 吴瑜         | 核对          | 吴路方 | 型号           |               | YG-14-F4 (2) |      |
|      |      |                      |       | ANGULAR            | $\pm 5^\circ$ | 日期            | 2011.09.23 | 核准          | 周培雷 | 图号           |               | 144F(2.0)    |      |
|      |      |                      |       |                    |               | DATE          |            | APPROVAL BY |     | DRG NO.      |               |              |      |