

RoHS Compliant  
2002/95/EC





### PCB. 焊接图

PCB WELDING DRAWING

### 主要技术参数、性能

额定电流、电压	0.3A DC30V
接触电阻	≤100mΩ
绝缘电阻	≥100MΩ
耐电压	500VAC
插拔力	3-30N
寿命	5000次
温度范围	-20℃~70℃
湿度范围	-40℃~85℃



Model No.	C	E
CENTER PIN	φ1.0	φ1.3

6	Pin	Brass	1	Ni Plated	0.5~2	±0.10	杨瑛平	产品名称	DC JACK
5	Cover	Nylon+F.G	1	Black	2~5	±0.25	郑金钰	产品型号	YG-DCE0-3130A
4	Terminal	Brass Strip	1	Ag Plated	5~10	±0.30	林进生	日期	2023.05.19
3	Spring terminal	SUS	1	Ag Plated	ANGLE	±3°	1:1	UNIT	mm
2	Terminal	Brass Strip	1	Ag Plated	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.				
1	Case	Nylon+F.G	1	Black					
项目	名称	材质	数量	表面处理/颜色	东莞市铨高电子有限公司				