

RoHS Compliant
2002/95/EC





PCB. 焊接图

PCB WELDING DRAWING

主要技术参数、性能

额定电流、电压	0.3A DC30V
接触电阻	≤100mΩ
绝缘电阻	≥100MΩ
耐电压	500VAC
插拔力	3-30N
寿命	5000次
温度范围	-20℃~70℃
湿度范围	-40℃~85℃

6	一般公差	0.5~2	±0.10	审核	杨瑛平	产品名称	DC JACK
5	Terminal	Ag Plated	±0.25	批准	郑金钰	产品型号	YG-DCE0-2110A
4	Spring terminal	Ag Plated	±0.30	SHEET	林进生	日期	2023.05.19
3	Cover	Black	ANGLE	1:1	UNIT	mm	
2	Plug Pin	Ni Plated	±3°	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			
1	Case	Black	数量	东莞市铷高电子制品有限公司			
项目	名称	表面处理/颜色	材质				



Model No.	H	I	J
CENTER PIN	∅2.0	∅2.35	∅2.5
PLUG O.D.	2.05 ^{+0.10} _{-0.00}	2.40 ^{+0.10} _{-0.00}	2.55 ^{+0.10} _{-0.00}